Date of Revision: April 16, 2015



SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION **Product Name:** GST International 24 Hour Emergency: Elephant Armor Primer INFOTRAC: 1-800-535-5053 Contract 93918 **Company Name: GST** International. Inc. Outside U.S. and Canada Company Address: 994 Packer Way Infotrac: 352-323-3500 Company Address Cont: Sparks, NV 89434 NOTE: INFOTRAC and National Response Center Business Phone: 775/829-2626 emergency numbers to be used only in the event of Website: www.gstinternational.com chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals Recommended Use: Primer for Mortar SECTION 2 – HAZARDS IDENTIFICATION

Hazard Classification: This material is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Other hazards:

No data available.

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

| Component | CASRN | Concentration | |
|--------------------|---------------|---------------|--|
| Acrylic polymer(s) | Not hazardous | 46.0-48.0% | |
| Residual monomers | Not available | < 0.05% | |
| Water | 7732-18-5 | 52.0 -54.0% | |

SECTION 4 – FIRST AID MEASURES

Description of first aid measures

Inhalation: Move to fresh air.

Skin contact: Wash with water and soap as a precaution. If skin irritation persists, call a physician. **Eye contact:** Rinse with plenty of water. If eye irritation persists, consult a specialist. **Ingestion:** Drink 1 or 2 glasses of water. Consult a physician if necessary. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed: Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.



Global Sealer

Technologies

SECTION 5 – FIRE FIGHTING MEASURES

Suitable extinguishing media: Use extinguishing media appropriate for surrounding fire. Unsuitable extinguishing media: no data available

Special hazards arising from the substance or mixture Hazardous combustion products: no data available

Unusual Fire and Explosion Hazards: Material can splatter above 100C/212F. Dried product can burn.

Advice for firefighters

Fire Fighting Procedures: no data available

Special protective equipment for firefighters: Wear self-contained breathing apparatus and protective suit.

SECTION 6 – ACCIDENTAL RELEASE MEASURES (STEPS FOR SPILLS)

Personal precautions, protective equipment and emergency procedures: Use personal protective equipment. Keep people away from and upwind of spill/leak. Material can create slippery conditions.

Environmental precautions: CAUTION: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

Methods and materials for containment and cleaning up: Contain spills immediately with inert materials (e.g., sand, earth). Transfer liquids and solid diking material to separate suitable containers for recovery or disposal.

SECTION 7 - HANDLING AND STORAGE

<u>Precautions for safe handling:</u> Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep container tightly closed. Do not breathe vapors, mist or gas.

Conditions for safe storage: Keep from freezing - product stability may be affected. STIR WELL BEFORE USE.

Storage stability

Storage temperature: 1 - 49 °C (34 - 120 °F)

Other data: Monomer vapors can be evolved when material is heated during processing operations. See SECTION 8, for types of ventilation required.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure limits are listed below, if they exist.

Exposure controls

Engineering controls: Use local exhaust ventilation with a minimum capture velocity of 100 ft/min. (0.5 m/sec.) at the point of vapor evolution. Refer to the current edition of Industrial Ventilation: A



Global Sealer

Technologies

Manual of Recommended Practice published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Protective measures: Facilities storing or utilizing this material should be equipped with an eyewash facility.

Individual protection measures

Eye/face protection: Safety glasses with side-shields Eye protection worn must be compatible with respiratory protection system employed. **Skin protection**

Hand protection: The glove(s) listed below may provide protection against permeation. (Gloves of other chemically resistant materials may not provide adequate protection): Neoprene gloves

Respiratory protection: A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements or equivalent must be followed whenever workplace conditions warrant a respirator's use. None required under normal operating conditions. Where vapors and/or mists may occur, wear a properly fitted NIOSH approved (or equivalent) half-mask, airpurifying respirator. Air-purifying respirators should be equipped with NIOSH approved (or equivalent) organic vapor cartridges and N95 filters. If oil mist is present, use R95 or P95 filters.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state: liquid Color: Milky white Odor: acrylic-like Odor Threshold: no data available **pH:** 9.3 - 10.2 Melting point/range: 0 °C (32 °F) Water Freezing point: no data available Boiling point: (760 mmHg) 100 °C (212 °F) Water Flash point: Noncombustible Evaporation Rate (Butyl Acetate = 1): <1 Water Flammability (solid, gas): Not Applicable Lower explosion limit: Not applicable Upper explosion limit: Not applicable Vapor Pressure: 17 mmHg at 20 °C (68 °F) Water Relative Vapor Density (air = 1): <1 Water Relative Density (water = 1): 1.0 - 1.2 Water solubility: Dilutable Partition coefficient n-octanol/water: no data available Auto-ignition temperature: Not applicable Decomposition temperature: no data available Dynamic Viscosity: 10 - 60 mPa.s Kinematic Viscosity: no data available Explosive properties: no data available Oxidizing properties: no data available



Global Sealer

Technologies

Molecular weight: no data available Percent volatility: 52 - 54 % Water

NOTE: The physical data presented above are typical values and should not be construed as a specification.

SECTION 10 – STABILITY AND REACTIVITY

Reactivity: no data available

Chemical stability: Stable

Possibility of hazardous reactions: None known. Product will not undergo polymerization.

Conditions to avoid: no data available

Incompatible materials: There are no known materials which are incompatible with this product. Hazardous decomposition products: Thermal decomposition may yield acrylic monomers.

SECTION 11 – TOXICOLOGY INFORMATION

Toxicological information on this product or its components appear in this section when such data is available.

Acute toxicity Acute oral toxicity LD50, Rat, > 5,000 mg/kg Acute dermal toxicity LD50, Rabbit, > 5,000 mg/kg Acute inhalation toxicity Product test data not available. Skin corrosion/irritation May cause transient irritation. Serious eye damage/eye irritation No eye irritation Sensitization Product test data not available. Specific Target Organ Systemic Toxicity (Single Exposure) Product test data not available. Specific Target Organ Systemic Toxicity (Repeated Exposure) Product test data not available. Carcinogenicity Product test data not available. Teratogenicity Product test data not available. **Reproductive toxicity**



Global Sealer

Technologies

Product test data not available. **Mutagenicity** Product test data not available. **Aspiration Hazard** Product test data not available. **Additional information** No data are available for this material. The information shown is based on profiles of compositionally similar materials.

COMPONENTS INFLUENCING TOXICOLOGY: Acrylic polymer(s) Acute inhalation toxicity The LC50 has not been determined. Residual monomers Acute inhalation toxicity The LC50 has not been determined.

SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicological information on this product or its components appear in this section when such data is available.

General Information

There is no data available for this product.

Toxicity Acrylic polymer(s) Acute toxicity to fish No relevant data found. Residual monomers Acute toxicity to fish No relevant data found.

Persistence and degradability Acrylic polymer(s) Biodegradability: No relevant data found. Residual monomers Biodegradability: No relevant data found.

Bioaccumulative potential Acrylic polymer(s) Bioaccumulation: No relevant data found. Residual monomers Bioaccumulation: No relevant data found.

Mobility in soil Residual monomers No relevant data found.



Global Sealer

Technologies

SECTION 13 – DISPOSAL CONSIDERATIONS

Disposal methods: Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. For disposal, incinerate or landfill at a permitted facility in accordance with local, state, and federal regulations.

SECTION 14 - TRANSPORTATION INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Not regulated for transport

Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code: Consult IMO regulations before transporting ocean bulk Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transportation of the material.

SECTION 15 – REGULATORY INFORMATION

OSHA Hazard Communication Standard

This product is considered non-hazardous under the OSHA Hazard Communication Standard (29CFR1910.1200).

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

This product is not a hazardous chemical under 29CFR 1910.1200, and therefore is not covered by Title III of SARA.

<u>Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313</u>

This product does not contain a chemical which is listed in Section 313 at or above de minimis concentrations.

Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

Releases of this material to air, land, or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) or to



Global Sealer

Technologies

state and local emergency planning committees under the Superfund Amendments and Reauthorization Act (SARA) Title III Section 304.

<u>Pennsylvania</u>

Any material listed as "Not Hazardous" in the CAS REG NO. column of SECTION 2, Composition/Information On Ingredients, of this MSDS is a trade secret under the provisions of the Pennsylvania Worker and Community Right-to-Know Act.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SECTION 16 – OTHER INFORMATION

Hazard Rating System HMIS Health - 1 Flammability - 0

Physical Hazard - 0

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of the need that information is current, applicable and suited to the circumstances of use. This safety sheet cannot cover all possible situations which the user may experience during processing. Each aspect of your operation should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. GST International assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, GST International assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Compliance with all applicable federal, state, and local laws and local regulations remains the responsibility of the user.

END OF SDS SHEET